

SDSD6189

ITEM: 1EZHZ - Lock De-Icer/Lubricant, Clear

DELIVERY: 6420979834

HU NUMBER: U810410881

SAFETY DATA SHEET (SDS)

This SDS should be attached or kept with the respective product with which it is associated.

SDS - D6189

Associated Items
1EZHZ
SAFETY DATA SHEET
LOCK DE-ICER
VERSION: 2.1
UPDATE: 11/13/2014

PO-65663
Grainger

-----SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE -----
AND OF THE COMPANY/UNDERTAKING

1.1. PRODUCT IDENTIFIER:

PRODUCT NAME: LOCK DEICER
PRODUCT NO.: 00500-V; 05002-V; 00502-V; 00500-VCS12; 00500-VFB24

1.2. RELEVANT IDENTIFIED USES OF THE SUBSTANCE OR MIXTURE AND USES ADVISED AGAINST:

IDENTIFIED USES: LOCK DEICER

1.3. DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET:

IMPORTER:
BELL AUTOMOTIVE PRODUCTS, INC.
18940 N. PIMA ROAD
SUITE 200
SCOTTSDALE, AZ 85255

TEL: 888.694.2355

FAX: 480.991.5595

RLEE@BELLAUTOMOTIVE.COM

MANUFACTURE:
SHIEUN TA INDUSTRY CO., LTD.
NO. 34-12, LANE 194
CHUNG CHENG 3RD RD
YING KO DISTRICT
NEW TAIPEI CITY
TAIWAN

TEL: +886 2 2670 7931

FAX: +886 2 2670 7914

SHIEUN-TA@UMAIL.HINET.NET

1.4. EMERGENCY TELEPHONE NUMBER:
USA: 888.694.2355
INTERNATIONAL: +886 2 2670 793

-----SECTION 2: HAZARDS IDENTIFICATION -----

2.1. CLASSIFICATION OF THE SUBSTANCE OR MIXTURE:

FLAMMABLE AEROSOLS, CATEGORY 2
EYE IRRITATION, CATEGORY 2A

2.2. LABEL ELEMENTS:

SYMBOL:
GHS02: FLAME
GHS07: EXCLAMATION MARK

SIGNAL WORD: DANGER

HAZARD STATEMENTS:
EXTREMELY FLAMMABLE AEROSOLS.
CAUSES SERIOUS EYE IRRITATION.
MAY CAUSE DROWSINESS OR DIZZINESS.

PRECAUTIONARY STATEMENTS:

GENERAL PRECAUTIONARY STATEMENTS:
IF MEDICAL ADVICE IS NEEDED, HAVE PRODUCT CONTAINER OR LABEL AT HAND.
KEEP OUT OF REACH OF CHILDREN.
READ LABEL BEFORE USE.

PREVENTION PRECAUTIONARY STATEMENTS:
KEEP AWAY FROM HEAT, HOT SURFACES, OPEN FLAMES, SPARKS. - NO SMOKING.
AVOID BREATHING MIST, SPRAY, VAPOURS.
USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA.

RESPONSE PRECAUTIONARY STATEMENTS:

IF INHALED:
REMOVE VICTIM TO FRESH AIR AND KEEP AT REST IN A POSITION COMFORTABLE FOR BREATHING.

IF IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES.

IF EYES IRRITATION PERSISTS: GET MEDICAL ADVICE/ATTENTION.

STORAGE PRECAUTIONARY STATEMENTS:
STORE IN A WELL VENTILATED PLACE.
STORE AT TEMPERATURES NOT EXCEEDING 50 DEG. C/122 DEG. F
DO NOT EXPOSE TO TEMPERATURES EXCEEDING 50 DEG. C/122 DEG. F

DISPOSAL PRECAUTIONARY STATEMENTS:
DISPOSE OF CONTENTS/CONTAINER TO COMPLY WITH LOCAL, STATE AND FEDERAL REGULATIONS.

2.3. OTHER HAZARDS: NO DATA AVAILABLE.

-----SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS -----

IDENTIFICATION	NAME	CLASSIFICATION	W/W %
CAS: 67-63-0 EC: 200-661-7	ISOPROPYL ALCOHOL	FLAM. LIQ.2, H225 EYE IRRIT.2, H319; STOT SE3, H336	95.0 - 97.0
CAS: 8042-47-5 EC: 232-455-8	MINERAL OIL	NOT CLASSIFIED.	1.0 - 2.5
CAS: 124-38-9 EC: 204-695-9	CARBON DIOXIDE	PRESS. GAS; H280	1.0 - 5.0
TOTAL		100.0	

THE FULL TEXT FOR ALL R-PHRASES AND HAZARD STATEMENTS ARE DISPLAYED IN SECTION 16.

-----SECTION 4: FIRST AID MEASURES -----

4.1. DESCRIPTION OF FIRST AID MEASURES:

FIRST-AID MEASURES GENERAL:
CHECK THE VITAL FUNCTIONS.

UNCONSCIOUS: MAINTAIN ADEQUATE AIRWAY AND RESPIRATION.

RESPIRATORY ARREST: ARTIFICIAL RESPIRATION OR OXYGEN.

CARDIAC ARREST: PERFORM RESUSCITATION.

VICTIM CONSCIOUS WITH LABOURED BREATHING: HALF-SEATED.

VICTIM IN SHOCK: ON HIS BACK WITH LEGS SLIGHTLY RAISED.

VOMITING:
PREVENT ASPHYXIA/ASPIRATION PNEUMONIA. PREVENT COOLING BY COVERING THE VICTIM (NO WARMING UP). KEEP WATCHING THE VICTIM. GIVE PSYCHOLOGICAL AID. KEEP THE VICTIM CALM, AVOID PHYSICAL STRAIN.

DEPENDING ON THE VICTIM'S CONDITION:
DOCTOR/HOSPITAL. NEVER GIVE ALCOHOL TO DRINK.

FIRST-AID MEASURES AFTER INHALATION: REMOVE THE VICTIM INTO FRESH AIR.
RESPIRATORY PROBLEMS: CONSULT A DOCTOR/MEDICAL SERVICE.

FIRST-AID MEASURES AFTER SKIN CONTACT:
RINSE WITH WATER. SOAP MAY BE USED. DO NOT APPLY (CHEMICAL) NEUTRALIZING AGENTS. TAKE VICTIM TO A DOCTOR IF IRRITATION PERSISTS.

FIRST-AID MEASURES AFTER EYE CONTACT:
RINSE IMMEDIATELY WITH PLENTY OF WATER. DO NOT APPLY NEUTRALIZING AGENTS. TAKE VICTIM TO AN OPHTHALMOLOGIST IF IRRITATION PERSISTS.

FIRST-AID MEASURES AFTER INGESTION: RINSE MOUTH WITH WATER.

IMMEDIATELY AFTER INGESTION:
GIVE LOTS OF WATER TO DRINK. DO NOT INDUCE VOMITING. GIVE ACTIVATED CHARCOAL. CALL POISON INFORMATION CENTRE. CONSULT A DOCTOR/MEDICAL SERVICE IF YOU FEEL UNWELL.

INGESTION OF LARGE QUANTITIES: IMMEDIATELY TO HOSPITAL.

DOCTOR: GASTRIC LAVAGE.

4.2. MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:

SYMPTOMS/INJURIES AFTER INHALATION:

EXPOSURE TO HIGH CONCENTRATIONS:
COUGHING. DRY/SORE THROAT. CENTRAL NERVOUS SYSTEM DEPRESSION. DIZZINESS. HEADACHE. NARCOSIS.

SYMPTOMS/INJURIES AFTER SKIN CONTACT: DRY SKIN.

SYMPTOMS/INJURIES AFTER EYE CONTACT: IRRITATION OF THE EYE TISSUE

SYMPTOMS/INJURIES AFTER INGESTION:

AFTER ABSORPTION OF HIGH QUANTITIES:
CENTRAL NERVOUS SYSTEM DEPRESSION. HEADACHE. DILATION OF THE BLOOD VESSELS. LOW ARTERIAL PRESSURE. NAUSEA. VOMITING. ABDOMINAL PAIN. DISTURBED MOTOR RESPONSE. DISTURBANCES OF CONSCIOUSNESS.

FOLLOWING SYMPTOMS MAY APPEAR LATER:

RECEIVED
JAN 29 2019
MAINTENANCE DEPT



BODY TEMPERATURE FALL. SLOWING RESPIRATION.

CHRONIC SYMPTOMS:
ON CONTINUOUS/REPEATED EXPOSURE/CONTACT:
RED SKIN, DRY SKIN, ITCHING, CRACKING OF THE SKIN, SKIN RASH/INFLAMMATION,
IMPAIRED MEMORY.

4.3. INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT
NEEDED: NO ADDITIONAL INFORMATION AVAILABLE.

-----SECTION 5: FIRE-FIGHTING MEASURES -----

5.1. EXTINGUISHING MEDIA:

EXTINGUISHING MEDIA:
USE: FOAM, CARBON DIOXIDE OR DRY POWDER.

UNSUITABLE EXTINGUISHING MEDIA:
DO NOT USE WATER JET AS AN EXTINGUISHER.

5.2. SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:

HAZARDOUS COMBUSTION PRODUCTS:
DURING FIRE, TOXIC GASES (CO, CO2) ARE FORMED.

UNUSUAL FIRE & EXPLOSION HAZARDS:
EXTREMELY FLAMMABLE. AEROSOL CANS MAY EXPLODE IN A FIRE.

SPECIFIC HAZARDS:
WHEN HEATED AND IN CASE OF FIRE, HARMFUL VAPOURS/GASES MAY BE FORMED.

5.3. ADVICE FOR FIRE-FIGHTERS:

SPECIAL FIRE FIGHTING PROCEDURES:
COOL CONTAINERS EXPOSED TO FLAMES WITH WATER UNTIL WELL AFTER THE FIRE IS
OUT.

PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS:
SELF-CONTAINED BREATHING APPARATUS AND FULL PROTECTIVE CLOTHING MUST BE
WORN IN CASE OF FIRE.

-----SECTION 6: ACCIDENTAL RELEASE MEASURES -----

6.1. PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

6.1.1. FOR NON-EMERGENCY PERSONNEL:

PROTECTIVE EQUIPMENT: GLOVES, PROTECTIVE GOGGLES.

EMERGENCY PROCEDURES:
KEEP UPWIND. MARK THE DANGER AREA. CONSIDER EVACUATION. SEAL OFF LOW-LYING
AREAS. CLOSE DOORS AND WINDOWS OF ADJACENT PREMISES. NO SMOKING. NO NAKED
FLAMES OR SPARKS. SPARK- AND EXPLOSIONPROOF APPLIANCES AND LIGHTING
EQUIPMENT. USE NON-SPARKING TOOLS.

6.1.2. FOR EMERGENCY RESPONDERS:

PROTECTIVE EQUIPMENT:
EQUIP CLEANUP CREW WITH PROPER PROTECTION. DO NOT BREATHE GAS, FUMES,
VAPOUR OR SPRAY.

EMERGENCY PROCEDURES:
STOP LEAK IF SAFE TO DO SO. VENTILATE AREA. IF A MAJOR SPILL OCCURS, ALL
PERSONNEL SHOULD BE IMMEDIATELY EVACUATED AND THE AREA VENTILATED.

6.2. ENVIRONMENTAL PRECAUTIONS: PREVENT SPREADING IN SEWERS.

6.3. METHODS AND MATERIAL FOR CONTAINMENT AND CLEANING UP:

FOR CONTAINMENT:
CONTAIN RELEASED SUBSTANCE, PUMP INTO SUITABLE CONTAINERS. CONSULT
"MATERIAL-HANDLING" TO SELECT MATERIAL OF CONTAINERS. DAM UP THE LIQUID
SPILL. TRY TO REDUCE EVAPORATION. DILUTE/DISPERSE COMBUSTIBLE GAS/VAPOUR
WITH WATER CURTAIN. PROVIDE EQUIPMENT/RECEPTACLES WITH EARTHING.

METHODS FOR CLEANING UP:
TAKE UP LIQUID SPILL INTO ABSORBENT MATERIAL, E.G.:
DRY SAND/EARTH/VERMICULITE OR POWDERED LIMESTONE. DO NOT USE COMPRESSED AIR
FOR PUMPING OVER SPILLS. CAREFULLY COLLECT THE SPILL/LEFTOVERS. CLEAN
CONTAMINATED SURFACES WITH AN EXCESS OF WATER. WASH CLOTHING AND EQUIPMENT
AFTER HANDLING.

6.4. REFERENCE TO OTHER SECTIONS:

SEE SECTION 7 FOR INFORMATION ON SAFE HANDLING.
SEE SECTION 8 FOR INFORMATION ON PERSONAL PROTECTION EQUIPMENT.
SEE SECTION 13 FOR DISPOSAL INFORMATION.

-----SECTION 7: HANDLING AND STORAGE -----

7.1. PRECAUTIONS FOR SAFE HANDLING:
PROVIDE GOOD VENTILATION. AVOID CONTACT WITH EYES. WASH HANDS AFTER
HANDLING.

7.2. CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES:
KEEP AWAY FROM HEAT, SPARKS AND OPEN FLAME.

AEROSOL CANS:
MUST NOT BE EXPOSED TO DIRECT SUNLIGHT OR TEMPERATURES ABOVE 50 DEG. C.

7.3. SPECIFIC END USE(S):
THE IDENTIFIED USES FOR THIS PRODUCT ARE DETAILED IN SECTION 1.2.

-----SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION -----

8.1. CONTROL PARAMETERS:

ISOPROPYL ALCOHOL (67-63-0):
USA ACGIH TWA: 200 PPM
USA ACGIH STEL: 400 PPM
OSHA PEL (TWA): 980 MG/M3
OSHA PEL (TWA): 400 PPM

8.2. EXPOSURE CONTROLS:

ENGINEERING MEASURES: PROVIDE ADEQUATE VENTILATION.

PERSONAL PROTECTIVE EQUIPMENT:
GLOVES, SAFETY GLASSES. AVOID ALL UNNECESSARY EXPOSURE.

HAND PROTECTION:
FOR PROLONGED OR REPEATED SKIN CONTACT USE SUITABLE PROTECTIVE GLOVES.

EYE PROTECTION:
WEAR APPROVED CHEMICAL SAFETY GOGGLES WHERE EYE EXPOSURE IS REASONABLY
PROBABLE.

RESPIRATORY PROTECTION:
WHERE EXPOSURE THROUGH INHALATION MAY OCCUR FROM USE, RESPIRATORY
PROTECTION EQUIPMENT IS RECOMMENDED.

-----SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES -----

9.1. INFORMATION ON BASIC PHYSICAL AND CHEMICAL PROPERTIES:
THIS PRODUCT IS A COLORLESS LIQUID IN A PRESSURIZED CAN (AEROSOL CAN), WITH
CARBON DIOXIDE AS A PROPPELLANT. THE FOLLOWING VALUES ARE FOR THE MAIN
COMPONENT-ISOPROPYL ALCOHOL (67-63-0)

APPEARANCE: CLEAR LIQUID.

ODOR: ALCOHOL ODOR

SPECIFIC GRAVITY: 0.786

PH AS SUPPLIED: N/A

BOILING POINT (DEG. F): 180 (AT 760 MMHg.)

MELTING POINT (DEG. F): -127

FLASH POINT: 12 DEG. C

EVAPORATION RATE (N-BUTYL ACETATE=1): 1.5

VAPOR PRESSURE (MMHg): 33 (AT 68 DEG. F)

VAPOR DENSITY (AIR=1): 2.1

SOLUBILITY IN WATER: MISCIBLE.

9.2 OTHER INFORMATION:

VOC CONTENT: >96%

-----SECTION 10: STABILITY AND REACTIVITY -----

10.1. REACTIVITY:
NO SPECIFIC REACTIVITY HAZARDS ASSOCIATED WITH THIS PRODUCT.
IEZH2

10.2. CHEMICAL STABILITY:
STABLE UNDER NORMAL TEMPERATURE CONDITIONS AND RECOMMENDED USE.

10.3. POSSIBILITY OF HAZARDOUS REACTIONS:
HAZARDOUS POLYMERISATION: WILL NOT POLYMERISE.

10.4. CONDITIONS TO AVOID:
AVOID HEAT, FLAMES AND OTHER SOURCES OF IGNITION.

10.5. INCOMPATIBLE MATERIALS: STRONG ACIDS, STRONG BASES.

10.6. HAZARDOUS DECOMPOSITION PRODUCTS: NONE UNDER NORMAL CONDITIONS.

-----SECTION 11: TOXICOLOGICAL INFORMATION -----

11.1. INFORMATION ON TOXICOLOGICAL EFFECTS:

ACUTE TOXICITY:

ISOPROPYL ALCOHOL (67-63-0):
LD50 ORAL RAT: 5045 MG/KG (RAT)
LD50 DERMAL RABBIT: 12870 MG/KG (RABBIT)
LC50 INHALATION RAT (MG/L): 73 MG/L/4H (RAT)

MINERAL OIL (8042-47-5):
LD50 ORAL RAT: NOT AVAILABLE
LD50 DERMAL RABBIT: NOT AVAILABLE
LC50 INHALATION RAT (MG/L): NOT AVAILABLE

CARBON DIOXIDE (124-38-9):
LD50 ORAL RAT: NOT AVAILABLE
LD50 DERMAL RABBIT: NOT AVAILABLE
LC50 INHALATION RAT (MG/L): NOT AVAILABLE

SKIN CORROSION/IRRITATION: NOT CLASSIFIED

SERIOUS EYE DAMAGE/IRRITATION: CAUSES EYE IRRITATION.

RESPIRATORY OR SKIN SENSITIZATION: NOT CLASSIFIED

GENOTOXICITY: NOT CLASSIFIED



CAFCINOGENICITY: NOT CLASSIFIED

REPRODUCTIVE TOXICITY: NOT CLASSIFIED

SYMPTOMS/INJURIES AFTER INHALATION:
EXPOSURE TO HIGH CONCENTRATIONS:
COUGHING, DRY/SORE THROAT, CENTRAL NERVOUS SYSTEM DEPRESSION, DIZZINESS,
HEADACHE, NARCOSIS.

SYMPTOMS/INJURIES AFTER SKIN CONTACT: DRY SKIN.

SYMPTOMS/INJURIES AFTER EYE CONTACT: IRRITATION OF THE EYE TISSUE.

SYMPTOMS/INJURIES AFTER INGESTION:
AFTER ABSORPTION OF HIGH QUANTITIES: CENTRAL NERVOUS SYSTEM DEPRESSION.

HEADACHE, DILATION OF THE BLOOD VESSELS, LOW ARTERIAL PRESSURE, NAUSEA,
VOMITING, ABDOMINAL PAIN, DISTURBED MOTOR RESPONSE, DISTURBANCES OF
CONSCIOUSNESS.

FOLLOWING SYMPTOMS MAY APPEAR LATER:
BODY TEMPERATURE FALL, SLOWING RESPIRATION.

CHRONIC SYMPTOMS:
ON CONTINUOUS/REPEATED EXPOSURE/CONTACT:
RED SKIN, DRY SKIN, ITCHING,
CRACKING OF THE SKIN, SKIN RASH/INFLAMMATION, IMPAIRED MEMORY.

-----SECTION 12: ECOLOGICAL INFORMATION -----

ECOTOXICITY:
THIS PRODUCT IS NOT EXPECTED TO BE HAZARDOUS TO THE ENVIRONMENT.

12.1. TOXICITY:

ECOLOG - GENERAL: NOT AVAILABLE.

ECOLOG - AIR: NOT AVAILABLE.

ECOLOG - WATER:
GROUND WATER POLLUTANT, NOT HARMFUL TO FISHES (LC50(96H) >1000 MG/L),
NOT HARMFUL TO INVERTEBRATES (DAPHNIA) (EC50 (48H) >1000 MG/L),
NOT HARMFUL TO ALGAE (EC50 (72H) >1000 MG/L).

ISOPROPYL ALCOHOL (67-63-0):

LC50 FISHES 1: 4200 MG/L (96 H; RASBORA HETEROMORPHA; FLOW-THROUGH SYSTEM)

EC50 DAPHNIA 1: >10000 MG/L (48 H; DAPHNIA MAGNA)

LC50 FISH 2: 9640 MG/L (96 H; PIMEPHALES PROMELAS; LETHAL)

EC50 DAPHNIA 2: 13299 MG/L (48 H; DAPHNIA MAGNA)

THRESHOLD LIMIT ALGAE 1:
>1000 MG/L (72 H; SCENEDESMUS SUBSPICATUS; GROWTH RATE)

THRESHOLD LIMIT ALGAE 2: 1800 MG/L (72 H; ALGAE; CELL NUMBERS)

MINERAL OIL (8042-47-5): NOT AVAILABLE

CARBON DIOXIDE (124-38-9): NOT AVAILABLE

12.2. PERSISTENCE AND DEGRADABILITY:

ISOPROPYL ALCOHOL (67-63-0):

PERSISTENCE AND DEGRADABILITY:
READILY BIODEGRADABLE IN WATER, BIODEGRADABLE IN THE SOIL.

BIODEGRADABLE IN THE SOIL UNDER ANAEROBIC CONDITIONS, NO (TEST) DATA ON
MOBILITY OF THE SUBSTANCE AVAILABLE.

BIOCHEMICAL OXYGEN DEMAND (BOD): 1.19 G O2/G SUBSTANCE

CHEMICAL OXYGEN DEMAND (COD): 2.23 G O2/G SUBSTANCE

THOD: 2.40 G O2/G SUBSTANCE

BOD (% OF THOD): 0.49% THOD

12.3. BIOACCUMULATIVE POTENTIAL:

ISOPROPYL ALCOHOL (67-63-0):
LOG POW: 0.05 (EXPERIMENTAL VALUE)
BIOACCUMULATIVE POTENTIAL: LOW POTENTIAL FOR BIOACCUMULATION (LOG KOW <4).

MINERAL OIL (8042-47-5): NOT AVAILABLE

CARBON DIOXIDE (124-38-9): NOT AVAILABLE

12.4. MOBILITY IN SOIL: NO FURTHER RELEVANT INFORMATION AVAILABLE.

12.5. RESULTS OF PBT AND VPVB ASSESSMENT:

PBT: NOT APPLICABLE.

VPVB: NOT APPLICABLE.

12.6. OTHER ADVERSE EFFECTS: NOT DETERMINED.

-----SECTION 13: DISPOSAL CONSIDERATIONS -----

WASTE TREATMENT METHODS:
DISPOSE OF WASTE AND RESIDUES IN ACCORDANCE WITH LOCAL AUTHORITY
REQUIREMENTS. MAKE SURE CONTAINERS ARE EMPTY BEFORE DISCARDING
(EXPLOSION RISK). RECOVER AND RECLAIM OR RECYCLE, IF PRACTICAL.

-----SECTION 14: TRANSPORT INFORMATION -----

14.1. UN NUMBER:
UN NO. (ADR/RID/ADN) 1950
UN NO. (I/DG) 1950
UN NO. (ICAO) 1950

14.2. UN PROPER SHIPPING NAME:
PROPER SHIPPING NAME: AEROSOLS

14.3. TRANSPORT HAZARD CLASS(ES):
ADR/RID/ADN CLASS 2

ADR/RID/ADN CLASS:
CLASS 2: GASES

ADR LABEL NO.: 2.1

I/DG CLASS: 2

ICAC CLASS/DIVISION: 2.1

TRANSPORT LABEL(S): CLASS 2.1, FLAMMABLE GASES

14.4. PACKING GROUP: PACKING GROUP II - MEDIUM DANGER

14.5. ENVIRONMENTAL HAZARDS:
ENVIRONMENTALLY HAZARDOUS SUBSTANCE/MARINE POLLUTANT: NO.

14.6. SPECIAL PRECAUTIONS FOR USER:
EMS (EMERGENCY SCHEDULES) CODE: F-D, S-U
TUNNEL RESTRICTION CODE: (D)

14.7. TRANSPORT IN BULK ACCORDING TO ANNEX II OF MARPOL73/78 AND THE IBC
CODE: NOT APPLICABLE.

-----SECTION 15: REGULATORY INFORMATION -----

15.1. SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS/LEGISLATION SPECIFIC FOR
THE SUBSTANCE OR MIXTURE:

U.S. FEDERAL REGULATIONS:
ALL INGREDIENTS OF THIS PRODUCT ARE LISTED, OR ARE EXEMPT FROM LISTING ON
THE TSCA INVENTORY. EXPORT NOTIFICATION IS REQUIRED UNDER TSCA SEC. 12-B.

REGULATORY STATUS OF HAZARDOUS CHEMICAL CONSTITUENTS OF THIS PRODUCT:

EXTREMELY TOXIC INGREDIENT 12B EXPORT NOTIFICATION
HAZARDOUS* CHEMICAL**

ISOPROPYL ALCOHOL NO NO REQUIRED
67-63-0

CARBON DIOXIDE NO NO NOT REQUIRED
124-38-9

WHITE MINERAL OIL NO NO NOT REQUIRED
8042-47-5

CONSULT THE APPROPRIATE REGULATIONS FOR EMERGENCY PLANNING AND RELEASE
REPORTING REQUIREMENTS FOR SUBSTANCES ON THE SARA SECTION 301 EXTREMELY
HAZARDOUS SUBSTANCE LIST.

**SUBSTANCES FOR WHICH THE "TOXIC CHEMICAL" COLUMN IS MARKED "YES" ARE ON
THE SARA SECTION 313 LIST OF TOXIC CHEMICALS, FOR WHICH RELEASE REPORTING
MAY BE REQUIRED. FOR SPECIFIC REQUIREMENTS, CONSULT THE APPROPRIATE
REGULATIONS.

SUPERFUND AMENDMENTS REAUTHORIZATION ACT (SARA) TITLE III:

SECTION 302 EXTREMELY HAZARDOUS SUBSTANCES (EHS): NONE

SECTION 311/312 HAZARD CATEGORIES:

FIRE HAZARD: YES
REACTIVE HAZARD: NO
RELEASE OF PRESSURE: YES

CALIFORNIA SAFE DRINKING WATER AND TOXIC ENFORCEMENT ACT (PROP 65):
THIS PRODUCT DOES NOT CONTAIN ANY CHEMICALS KNOWN TO THE STATE OF
CALIFORNIA TO CAUSE CANCER, BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

STATE RIGHT TO KNOW:
RHODE ISLAND, PENNSYLVANIA, FLORIDA, MINNESOTA, MASSACHUSETTS, NEW JERSEY,
TENNESSEE, ILLINOIS.

NAME CAS NO.
ISOPROPYL ALCOHOL 67-63-0

MINERAL OIL 8042-47-5

CARBON DIOXIDE 124-38-9

CANADIAN REGULATIONS:

CANADIAN DSL/NDSL INVENTORY STATUS:
THE COMPONENTS OF THIS PRODUCT ARE ON THE DSL INVENTORY.

CANADIAN ENVIRONMENTAL PROTECTION ACT (CEPA) PRIORITIES SUBSTANCES LISTS:
THE COMPONENTS OF THIS PRODUCT ARE NOT ON THE (CEPA) PRIORITIES LISTS.

CANADIAN WHMIS CLASSIFICATION AND SYMBOLS:
CLASS A: COMPRESSED GAS
CLASS B5: FLAMMABLE AEROSOLS
CLASS D22: SKIN OR EYE IRRITATION



15.2. CHEMICAL SAFETY ASSESSMENT:
NOT APPLICABLE, THIS PRODUCT IS A MIXTURE.

-----SECTION 16: OTHER INFORMATION -----

GENERAL INFORMATION:

AEROSOL: CAUTION:
PRESSURISED CONTAINER. PROTECT FROM SUNLIGHT. DO NOT EXPOSE TO TEMPERATURES EXCEEDING 50 DEG. C. DO NOT PIERCE OR BURN, EVEN AFTER USE. DO NOT SPRAY ON A NAKED FLAME OR ANY INCANDESCENT MATERIAL. KEEP OUT OF THE REACH OF CHILDREN. KEEP AWAY FROM SOURCES OF IGNITION - NO SMOKING.

SAFETY DATA SHEET STATUS:

REVISION DATE: NOV-13-2014

RISK PHRASES IN FULL:
R11 HIGHLY FLAMMABLE.
R36 IRRITATING TO EYES.
R67 VAPOURS MAY CAUSE DROWSINESS AND DIZZINESS.

HAZARD STATEMENTS IN FULL:

H222: EXTREMELY FLAMMABLE AEROSOLS.
H225: HIGHLY FLAMMABLE LIQUID AND VAPOUR.
H280: CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED.
H319: CAUSES SERIOUS EYE IRRITATION.
H336: MAY CAUSE DROWSINESS OR DIZZINESS.

STOT SE 3:
SPECIFIC TARGET ORGAN TOXICITY SINGLE EXPOSURE, CATEGORY 3, NARCOSIS

NFPA RATING:
NFPA HEALTH HAZARD 1 - EXPOSURE COULD CAUSE IRRITATION BUT ONLY MINOR RESIDUAL INJURY EVEN IF NO TREATMENT IS GIVEN.
NFPA FIRE HAZARD 3 - LIQUIDS AND SOLIDS THAT CAN BE IGNITED UNDER ALMOST ALL AMBIENT CONDITIONS.
NFPA REACTIVITY 0 - NORMALLY STABLE, EVEN UNDER FIRE EXPOSURE CONDITIONS, AND ARE NOT REACTIVE WITH WATER.

HMIS CLASSIFICATION:
HEALTH 1 SLIGHT HAZARD - IRRITATION OR MINOR REVERSIBLE INJURY POSSIBLE
FLAMMABILITY 3 SERIOUS HAZARD
PHYSICAL 0 MINIMAL HAZARD
PERSONAL PROTECTION B
SAFETY GLASSES
GLOVES

DISCLAIMER OF LIABILITY:
INFORMATION IN THIS SDS IS FROM AVAILABLE PUBLISHED SOURCES AND IS BELIEVED TO BE ACCURATE. NO WARRANTY, EXPRESS OR IMPLIED, IS MADE AND THE MANUFACTURER/DISTRIBUTOR ASSUMES NO LIABILITY RESULTING FROM THE USE OF THIS SDS. THE USER MUST DETERMINE SUITABILITY OF THIS INFORMATION FOR HIS APPLICATION.

